

2019 TRAILERING GUIDE

CHEVROLET



CENTURY
AUTO.CA

2 TABLE OF CONTENTS

3 SELECTING A VEHICLE/MAXIMUM TRAILER WEIGHT RATINGS

4 VEHICLES AND HITCHES

5 TRAILERING BASICS

6 IMPORTANT INFORMATION ABOUT TRAILERING

7 THINGS YOU SHOULD KNOW BEFORE YOU START TRAILERING

9 TRAILERING TECHNOLOGIES

11 SILVERADO 1500 CONVENTIONAL TRAILER WEIGHT RATINGS

12 SILVERADO HD CONVENTIONAL TRAILER WEIGHT RATINGS

**13 SILVERADO HD FIFTH-WHEEL/GOOSENECK TRAILER
WEIGHT RATINGS**

14 COLORADO, TAHOE AND SUBURBAN TRAILER WEIGHT RATINGS

15 TRAVERSE, BLAZER AND EQUINOX TRAILER WEIGHT RATINGS

**16 EXPRESS PASSENGER VAN AND EXPRESS CARGO VAN
TRAILER WEIGHT RATINGS**


**17 CHASSIS CAB AND EXPRESS CUTAWAY GROSS COMBINATION
WEIGHT RATINGS**

18 DINGHY TOWING

19 CLOSING REMARKS

3 SELECTING A VEHICLE/MAXIMUM TRAILER WEIGHT RATINGS¹ – lb. (kg)

The chart below gives you an idea of the maximum amount of weight you can confidently trailer with different Chevrolet models when your vehicle is properly equipped. See pages 11–16 for maximum trailer weight ratings by specific model.



¹ Before you buy a vehicle or use it for trailering, carefully review the Trailering section of the Owner's Manual. The weight of passengers, cargo and options or accessories may reduce the amount you can tow.


4 VEHICLES AND HITCHES




Hitch Ball on Step-Bumper




Hitch Ball on Draw Bar



Weight-Distributing Hitch with Sway Control



Fifth-Wheel Hitch



Gooseneck Hitch

SELECTING THE RIGHT HITCH Choosing the right hitch and making the proper electrical connections affects how your vehicle handles, corners and brakes, and allows you to alert other drivers of your intentions. Before selecting a hitch or trailering package, you should be familiar with the weight ratings specific to your Chevrolet vehicle, which are detailed on pages 11–16.

SELECTING TRAILERING EQUIPMENT Most Chevrolet vehicles offer a variety of standard and available equipment for enhanced trailering performance. Aside from the equipment described below, features such as heavy-duty cooling and extendable trailering mirrors may be available. See your Chevrolet dealer for more information on the model you're interested in.

WEIGHT-CARRYING HITCH This consists of a hitch ball mounted to a step-bumper or draw bar. Hitch balls are available in a range of sizes. Make sure that the diameter of your hitch ball matches your trailer coupler. Also check that the ball meets or exceeds the gross trailer weight rating.

WEIGHT-DISTRIBUTING HITCH This hitch type distributes the trailer tongue load by using spring bars to shift some of the hitch weight forward onto the tow vehicle's front axle and rearward to the trailer's axles.

FIFTH-WHEEL AND GOOSENECK HITCHES These are designed for heavy trailering. Located in the bed of the truck, these hitches position the trailer's kingpin weight over, or slightly in front of, the truck's rear axle. Fifth-wheel and gooseneck hitches are most frequently used with travel trailers, horse trailers and other large trailers.

HITCHES It's important to have the correct hitch equipment.

- If you'll be towing a trailer that requires a weight-distributing hitch, be sure to use a frame-mounted hitch platform of the proper size and capacity that is bolted to the frame and sway control of the proper size
- If you have to make any holes in the body of your vehicle to install a trailer hitch, be sure to seal the holes if you ever remove the hitch. If they're not sealed, dirt, water and deadly carbon monoxide from the exhaust can get into your vehicle

FIFTH-WHEEL TRAILERING Some Silverado models can be equipped with a fifth-wheel or gooseneck trailer hitch.

- Follow the manufacturer's directions for installation, but note that the hitch must be attached to the truck frame. Do not use the pickup bed for additional support. For proper kingpin tongue load distribution and control of the trailer, the hitch must be mounted so the kingpin load is placed over, or slightly ahead of, the rear axle centreline
- Fifth-wheel trailer kingpin loads are higher than conventional trailer tongue loads, so pay careful attention to the truck's payload capacity and Rear Gross Axle Weight Rating
- Your Chevrolet dealer can help you calculate the maximum allowable payload and GVWR required for your fifth-wheel trailering application. The weight of any additional equipment and all passengers, excluding driver and front passenger, must be subtracted from the payload weight to determine the maximum kingpin load available

WIRING HARNESS This allows you to connect the electrical components of your trailer, such as turn signals and brake lights, to the trailering vehicle. Select Silverado models and all Suburban and Tahoe models feature a 7-pin wiring harness to streamline hookup of trailer lighting and brakes, and a bussed electrical centre makes it easier to connect the integrated trailer brake controller.

TRAILER BRAKES Please review the vehicle's Owner's Manual and consult your local road authority for trailer brake requirements, as they vary by model and by Province or Territory. The most common trailer braking systems are surge brakes (found primarily on boat trailers) and electric brakes (often used on travel trailers, horse trailers and car haulers). Surge brakes are a self-contained hydraulic brake system on the trailer, activated during deceleration as the trailer coupler pushes on the hitch ball. An electric trailer brake system uses a brake control unit mounted inside the trailering vehicle; it operates by sensing the vehicle brakes and then applying the trailer brakes. An integrated electric trailer brake controller (option code JL1) is standard on Silverado 3500HD and available on Silverado 1500, Silverado 2500HD, Colorado, Tahoe and Suburban models.

SILVERADO SERIES In general, a higher series number in a model indicates a greater load-carrying capacity. In addition, a truck with a higher series number typically has a stronger frame, stiffer suspension and higher-capacity brakes, increasing the truck's ability to trailer heavy loads.

5 TRAILERING BASICS

Towing a trailer involves all major vehicle systems of your Chevrolet vehicle. Easy and confident trailering requires a properly equipped vehicle, additional trailering equipment and an appropriate trailer. It also requires loading both the vehicle and trailer properly, using safe driving techniques, meeting regional legal requirements, and following break-in and maintenance schedules. The vehicle owner is responsible for obtaining the proper equipment (including a hitch ball, hitch type of the proper size and capacity) required to safely tow both the trailer and the load that will be towed. For more information, consult your Owner’s Manual or speak to a trailering expert at your Chevrolet dealer. These charts will assist in determining how to best equip your Chevrolet vehicle for trailering. To help you understand the charts, consider these trailering factors:

RGAWR AND GVWR Addition of trailer hitch weight cannot cause vehicle weights to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR). These ratings can be found on the certification label located on the driver door or doorframe.

GCWR The Gross Combination Weight Rating is the total allowable weight of the completely loaded vehicle and trailer.

TRAILER WEIGHT RATING This rating is determined by subtracting the tow vehicle’s base weight (curb weight) from the Gross Combination Weight Rating (GCWR). Base vehicle (curb) weight plus 150 lb. (68 kg) each for the driver and a front passenger¹ is used, so additional passengers, optional equipment and cargo weight reduce this rating.

AXLE RATIO In general, a higher numerical axle ratio offers higher trailer weight ratings, quicker acceleration and less fuel efficiency. A lower numerical axle ratio offers better fuel efficiency and quieter vehicle operation but will have slower acceleration and lower trailer weight ratings.

NOTE The safety steps described here are by no means the only precautions to be taken when trailering. See the Owner’s Manual for your Chevrolet vehicle for additional guidelines and trailering tips.

TRAILERING CAUTION If you don’t use the correct equipment and drive properly, you can lose control of your vehicle when you pull a trailer. If the trailer is too heavy, your vehicle brakes may be less effective. You and your passengers could be seriously injured. Pull a trailer only after you have read the information in this guide and followed the steps on the following pages, consulted the Owner’s Manual, local road authorities and dealer.

TRAILER CLASSIFICATION	TYPICAL EXAMPLES	TYPICAL GROSS TRAILER WEIGHT EXAMPLES	TYPICAL HITCH TYPE ²
Light-Duty (I)	Folding camping trailer, snowmobiles and personal watercraft trailers (trailer and cargo combined)	Up to 2000 lb. (907 kg) gross trailer weight	Weight-carrying hitch
Medium-Duty (II)	Single-axle trailers up to 5.5 m (18 ft.), open utility trailers and small speedboats	2001–3500 lb. (908–1588 kg) gross trailer weight	Weight-carrying hitch
Heavy-Duty (III)	Dual- or single-axle trailers, larger boats and enclosed utility trailers	3501–5000 lb. (1588–2268 kg) gross trailer weight	Weight-carrying hitch ³ or weight-distributing hitch
Extra Heavy-Duty (IV)	Two-horse, travel and fifth-wheel recreational trailers	5001–10,000 lb. (2268–4536 kg) gross trailer weight	Weight-carrying hitch ³ ; weight-distributing hitch ³ ; fifth-wheel hitch or gooseneck hitch
Maximum Heavy-Duty (V)	Largest horse, travel and fifth-wheel recreational or commercial trailers	10,000 lb. (4536 kg) and above gross trailer weight	Weight-carrying hitch ³ ; weight-distributing hitch ³ ; fifth-wheel hitch or gooseneck hitch



¹ Front passenger weight not included on Tahoe, Suburban or Express. ² Represents minimum recommended hitches. Please refer to your trailer’s Owner’s Manual or ask your Chevrolet dealer. ³ Not required on Silverado 2500HD or 3500HD.

6 IMPORTANT INFORMATION ABOUT TRAILERING

The information below is intended to give you some details about the trailer ratings on your vehicle and a way to help determine that the vehicle you use can handle the load you want to pull.

TRAILER WEIGHT RATINGS AND GROSS COMBINATION

WEIGHT RATINGS Chevrolet engineers perform extensive testing of acceleration, handling, braking, thermal and structural performance to determine the Gross Combination Weight Rating (GCWR) and the trailer weight rating for your vehicle. The GCWR is the total allowable weight of the completely loaded vehicle and trailer including any passengers, cargo, equipment and conversions. You should not exceed the GCWR of your vehicle when you tow a trailer.

Chevrolet also calculates and publishes a trailer weight rating for each model or series of Chevrolet vehicles for comparison purposes. The trailer weight rating is not specific to an individual vehicle and is most useful for comparing product lines to one another to help you select a product that will meet your needs. **When you buy a vehicle, you should ensure that the total load (including passengers, cargo and equipment) you intend to pull with it will be less than the trailer weight rating of the vehicle.**

Because the trailer weight rating is calculated for a line of vehicles, rather than an individual load situation, some standardized assumptions are made when calculating the trailer weight rating. First, the base curb weight of that type of vehicle is used (the weight of a standard equipped vehicle without any options). Second, it is assumed that there is only a driver and a front passenger,¹ each weighing 150 lb. (68 kg). Third, it is assumed there is a certain tongue weight for the load (a tongue weight is the weight of only the tongue of the loaded trailer). For conventional trailering, a tongue weight that is 10% of the loaded trailer weight is used. For fifth-wheel/gooseneck trailering, a tongue weight that is a minimum of 15% of the loaded trailer weight is used. The actual trailer weight rating will vary.

HOW TO KEEP YOUR LOAD WITHIN THE CAPABILITIES OF YOUR VEHICLE

It is important that the combination of the tow vehicle and trailer does not exceed any of its weight ratings — GCWR, GVWR, FGAWR, RGAWR, trailer weight rating or tongue weight. The only way to be sure to not exceed any of these ratings is to weigh the tow vehicle and trailer combination, fully loaded for the trip, getting individual weights for each of these items. You can then subtract the weight of your vehicle from the GCWR. The difference between the two is the capacity you have available for your cargo, passengers, trailer, load and any other equipment you might use to set up your trailer. Put another way, your GCWR should always be greater than or equal to the weight of your vehicle, passengers, cargo, trailer (with equipment) and load.

The tongue weight for your trailer is the downward force of the coupler of the trailer on the vehicle hitch. You can calculate the tongue weight by placing the tongue of the trailer on an appropriate scale. For conventional trailering, the tongue weight should be 10% to 15% of the loaded trailer weight. For fifth-wheel/gooseneck trailering, the tongue weight should be a minimum of 15% of the loaded trailer weight.

The GVWR is the maximum amount the vehicle itself should weigh, including the as-equipped weight of the vehicle plus the cargo, passengers and trailer tongue weight. Put another way, the GVWR should always be greater than or equal to the weight of your vehicle, passengers, cargo and tongue weight.



¹ Front passenger weight not included on Tahoe, Suburban or Express.

7 THINGS YOU SHOULD KNOW BEFORE YOU START TRAILERING

BEFORE YOU TRAILER

SAFETY CHAINS Always attach safety chains between your vehicle and your trailer and cross them under the tongue of the trailer so that the tongue will be less likely to drop if the trailer should separate from the hitch. Leave enough slack in the chains so you can corner without the chains impeding the movement of the trailer. Do not allow safety chains to drag on the ground.

LOADING YOUR TRAILER Load your trailer to attain a 10%–15% tongue weight. Some specific trailer types (especially boat trailers) fall outside of this range. In these cases, the recommended tongue weight listed in the trailer Owner's Manual should be observed. A good rule of thumb is to distribute 60% of the load over the front half of the trailer and evenly from side to side. Loads sitting either too far forward or too far back in the trailer can create unstable trailering conditions – such as trailer sway – at highway speeds and during heavy braking. Once the trailer has been loaded and the weight is distributed properly, all cargo should be secured to prevent the load from shifting.

SAFETY CHECKLIST Before starting out on a trip, double-check the hitch and platform, the hitch nuts and bolts, mirror adjustments, safety chains, and vehicle and trailer lights. Make sure that a sway-control device is installed, if required, and that the device is working properly. Check tire pressure on both the tow vehicle and the trailer. If your trailer has electric brakes, test them by manually engaging the brake controller while the vehicle is moving slowly. Check to see that the breakaway switch, if available, is connected and functioning properly. Finally, make certain that all loads are secure.

ON THE ROAD

ACCELERATING/BRAKING Avoid overworking your engine when trailering by applying gradual pressure on the accelerator. Allow your vehicle to safely reach a comfortable driving speed. Give yourself extra time and room when merging onto highways. Braking when pulling a trailer requires extra distance. Allow ample room to come to a safe stop. A good measure for determining a safe following distance is to allow 3–4 seconds of space between you and the vehicle ahead. When braking, use firm, steady pressure on the brake pedal.

CONTROLLING TRAILER SWAY Sway refers to instability of the trailer relative to the tow vehicle, and often results from improper weight distribution, excessive speed or overloading. Other factors that can cause sway are crosswinds, poor vehicle maintenance and road conditions. Trying to steer out of sway will likely make it worse. Speed is a major contributor to trailer sway, so you need to slow the vehicle – braking, however, could lead to a jackknife or other loss of control. To help control sway, follow these steps:

TO HELP CONTROL SWAY

- If the trailer begins to sway, reduce vehicle speed by gradually removing your foot from the accelerator
- Pull your vehicle safely to the side of the road and attempt to determine the cause of the instability
- Check the trailer and vehicle to help correct possible causes, including an improperly or overloaded trailer, unrestrained cargo, improper trailer hitch configuration, or improperly inflated or incorrect vehicle or trailer tires

If the sway was caused by strong winds, wait for conditions to improve before continuing your trip.

Finally, some trailers can be equipped with anti-sway devices. Contact the manufacturer of your trailer for availability.

CORNERING The turning radius of a trailer is typically much smaller than that of your vehicle; therefore, a trailer may hit soft shoulders, curbs, trees or other objects when making tight turns. Taking turns sharply can also cause the trailer to strike against and damage the tow vehicle. When approaching a sharp corner, brake sooner than normal to reduce vehicle speed before entering the turn. Drive the vehicle slightly past the normal turning point then firmly turn the steering wheel. By cornering at a wider angle, both the vehicle and trailer should safely clear the inside of the turn.

PASSING When passing, allow additional time and distance to safely pass the other vehicle. Signal your intention to pass well in advance and, when reentering the lane after passing, make certain your trailer is clear of the vehicle you have passed. Never pass on hills or around curves.

BACKING UP To back up a trailer, place one hand at the six o'clock position on the steering wheel. To move the trailer to the left, move your hand to the left. To move the trailer to the right, move your hand to the right. Back up slowly and move the steering wheel in small increments to help maintain control. To assist in backing up, it is helpful to have someone outside the vehicle to guide you. Make certain you can see your spotter at all times.

DRIVING ON GRADES Before going down a steep grade, reduce your speed and shift the transmission into a lower gear. This provides “engine braking” and reduces the need to brake for long periods. Chevrolet crossover, SUV and pickup models equipped with a 6-speed automatic transmission, vans with 6-speed or 8-speed automatic, as well as pickups equipped with the available 8-speed or 10-speed automatic have a grade braking feature in the transmission which can do this for you. See your dealer or Owner's Manual for additional information. Pay attention to your temperature gauges for any signs of overheating.

8 THINGS YOU SHOULD KNOW BEFORE YOU START TRAILERING (CONTINUED)

OVERHEATING Prolonged driving with overheated fluids can cause damage to your vehicle. If temperature gauges register abnormally high, if there is a marked decrease in power or if you hear unusual engine noises, immediately take the following steps:

- Pull your vehicle safely to the side of the road. Once stopped, shift into Park (automatic transmission) or Neutral (manual transmission) and apply the parking brakes. Leave the engine running
- Turn off air conditioning and other accessories to reduce load on the engine. Roll down the windows and turn the heater on to maximum and the fan to its highest setting. The heater core provides a second cooling surface that can help reduce engine temperatures
- If you suspect that the overheating is the result of climbing a long, steep grade, run the engine at fast idle (around 1500 rpm) until the temperature gauge registers a normal reading

- With the vehicle in Park (automatic transmission) or Neutral (manual transmission), the parking brake engaged, and being mindful of traffic, exit your vehicle and look for steam or leaking coolant underneath the engine. If you see either of these, shut off the engine and allow the engine to cool. To avoid being burned, do not attempt to remove the radiator or coolant expansion tank cap until the engine has cooled sufficiently

PARKING ON GRADES Parking on steep grades with a trailer is not recommended; if you must, follow this procedure:

- Apply the brakes and shift into Neutral
- Have someone safely place trailer wheel blocks on the downgrade side
- Release the brakes until the blocks absorb the load
- Apply the parking brake and shift into Park (automatic transmission)

LEAVING YOUR PARKING SPOT ON GRADES

- Hold the brake pedal down and start the engine
- Shift into gear and release the parking brake
- Release brake and drive uphill slightly until free from the blocks
- Apply brakes and have someone safely retrieve the blocks



9 TRAILERING TECHNOLOGIES

TRAILERING PACKAGE An optional Trailering Equipment Package is available for a wide variety of Chevrolet models. The Z82 Package includes a trailer hitch platform and may include other trailering equipment.

TRAILER SWAY CONTROL Working in conjunction with the StabiliTrak® Electronic Stability Control System and integrated trailer brake controller (if equipped), the Trailer Sway Control feature on Colorado, Silverado, Suburban and Tahoe can sense trailer sway and can automatically apply the vehicle and trailer brakes and reduce engine power, if necessary, to help you get back on track.

HILL START ASSIST On inclines greater than a 5% grade, Hill Start Assist on Colorado, Silverado, Suburban, Tahoe, Traverse, Blazer, Equinox, Express Passenger, Express Cargo and Express Cutaway automatically engages to hold the vehicle stationary for about a second, allowing the driver time to press the accelerator before the vehicle can roll backward. It can be extremely helpful when you're stopped on a steep grade with a vehicle close to your rear bumper. The available integrated trailer brake controller will also assist with this feature and apply the trailer brakes.

STABILITRAK ELECTRONIC STABILITY CONTROL

When equipped, StabiliTrak helps improve vehicle stability, particularly during emergency manoeuvres. The StabiliTrak control module compares your steering input with the vehicle's actual response and then, if necessary, makes small, individual brake and engine torque applications to enhance control and help you keep on track. StabiliTrak automatically intervenes when it senses loss of lateral traction.

INTEGRATED TRAILER BRAKE CONTROLLER This is available on Silverado, Colorado, Suburban and Tahoe. Completely integrated within the electrical system, Anti-lock Braking System (ABS) and StabiliTrak, it allows your trailer's brakes to operate simultaneously with the vehicle's brakes.

REAR VISION CAMERA¹ This feature is designed to allow the driver to use the radio screen (if equipped) or the interior rear-view mirror to see certain stationary obstacles located behind the vehicle when travelling in reverse at low speeds. This feature is especially helpful when backing up to hitch your trailer.

TRAILERING CAMERA PACKAGE This available system integrates cameras into the side-view mirrors to provide a better visual down the sides of the trailer, help eliminate blind spots and make it easier to line up your trailer and hitch. Available on Silverado.

TOW/HAUL MODE Standard Tow/Haul mode on Express, Silverado, Suburban and Tahoe as well as available Tow/Haul mode on Colorado;² Traverse;³ Blazer⁴ and Equinox⁵ adjusts the shift schedule in the automatic transmission so it isn't "hunting" for the correct gear while towing or trailering.

AUTO GRADE BRAKING Standard on Equinox, Silverado, Suburban and Tahoe, this feature works with the cruise control to help maintain vehicle speed on long, steep grades.

CRUISE GRADE BRAKING Included with the 6-speed, 8-speed and 10-speed⁶ automatic transmission on Silverado, the cruise grade braking feature automatically downshifts to help slow the truck and preserve your brake pads on long, steep descents.

EXHAUST BRAKE SYSTEM This system is included on Silverado HD with the available Duramax 6.6L V8 Turbo-Diesel engine. After adjusting for the load and grade, the variable vane geometry turbo creates back pressure to slow the vehicle and help reduce brake use. That means reduced brake fade, prolonged brake life and more confidence when you're pulling up to 23,100 lb. (10,478 kg);⁷ especially on steep grades, increasing the vehicle's ability to trailer heavy loads. An exhaust brake system is also included on Colorado, Express Passenger and Express Cargo models with the available Duramax 2.8L Turbo-Diesel 4-cylinder engine.

AUTOMATIC LOCKING REAR DIFFERENTIAL This GM-exclusive feature intervenes when rear wheel slippage is detected at lower speeds. If one rear wheel slips, the locking rear axle automatically provides full lockup for maximum drive power to both rear wheels. Available on Colorado, Express, Tahoe, Suburban and Silverado models.

EXTENDABLE TRAILERING MIRRORS These vertical manual-folding and extendable mirrors have 329 cm² (51 sq. in.) of flat mirror surface and 158 cm² (24.5 sq. in.) of convex mirror surface to help you see what's happening around you. They are available as a factory option on Silverado HD or as a dealer-installed Chevrolet Accessory.

MAX TRAILERING PACKAGE Available on Silverado 1500, Tahoe and Suburban, the Max Trailering Package offers increased towing capability over the standard trailering package. See dealer for details.

¹ Safety or driver assistance features are no substitute for the driver's responsibility to operate the vehicle in a safe manner. The driver should remain attentive to traffic, surroundings and road conditions at all times. Visibility, weather and road conditions may affect feature performance. Read the vehicle Owner's Manual for more important feature limitations and information. ² With available 3.6L V6 engine or Duramax 2.8L Turbo-Diesel 4-cylinder engine. ³ Included with Trailering Package. ⁴ Requires All-Wheel Drive (AWD). ⁵ Included with available 2.0L 4-cylinder engine. ⁶ Available on Silverado 1500. ⁷ Requires Silverado 3500HD Crew Cab 2WD DRW model with available Duramax 6.6L V8 Turbo-Diesel engine and fifth-wheel hitch. Before you buy a vehicle or use it for trailering, carefully review the Trailering section of the Owner's Manual. The weight of passengers, cargo and options or accessories may reduce the amount you can tow.

CENTURY
CHEVROLET

10 TRAILERING TECHNOLOGIES (CONTINUED)

HITCH GUIDANCE WITH HITCH VIEW¹ A dynamic guiding line is integrated onto the image when you select Hitch Guidance on the Rear Vision Camera¹ screen. As an enhancement, available Hitch View allows you to zoom in on the hitch for a top-down view, making it easier to hook up your trailer on your own.

INDUSTRY-FIRST TRAILERING LABEL This small label has a big job. Located on the driver-side door jamb, it provides information that's specific to your vehicle and vital to towing, including GVWR², GCWR³, GAWR⁴ for the rear axle, maximum payload, maximum tongue weight and curb weight. Available on Silverado 1500.

INDUSTRY-FIRST ELECTRIC PARKING BRAKE HOOKUP ASSIST This feature automatically engages the parking brake when you shift into Park after you engage available Hitch View, helping to eliminate unintentional roll so your trailer and hitch stay in alignment. Available on Silverado 1500.

INDUSTRY-FIRST TRAILER THEFT ALERT With this available feature, if the harness on your attached trailer is disconnected, the lights will flash and the horn will sound. In addition, if you have an active OnStar[®] Safety & Security Plan⁵ and set up Theft Alarm Notification preferences, you can receive a notification by phone, text or email. Available on Silverado 1500.

myChevrolet APP[™] WITH TRAILERING This industry-first mobile app⁶ feature includes predeparture checklists, a glossary of trailering terms, how-to videos, trailer light tests and more. Available on Silverado 1500.

TRAILER TIRE PRESSURE MONITORING SYSTEM When you install the sensors, this available feature checks trailer tires for proper inflation and temperature⁷. Available on Silverado 1500.

IN-VEHICLE ADVANCED TRAILERING SYSTEM With a phone companion app you can create profiles for a number of trailers and also keep track of various trailer metrics. It also allows you to set maintenance reminders and conduct a trailer light test. Available on Silverado 1500.

¹ Safety or driver assistance features are no substitute for the driver's responsibility to operate the vehicle in a safe manner. The driver should remain attentive to traffic, surroundings and road conditions at all times. Visibility, weather and road conditions may affect feature performance. Read the vehicle Owner's Manual for more important feature limitations and information. ² Maximum Gross Vehicle Weight Rating (GVWR). When properly equipped; includes weight of vehicle, passengers, cargo and equipment. ³ Gross Combination Weight Rating. The maximum allowable weight for the vehicle and trailer, all equipment, total payload, fuel, fluids and passengers. ⁴ Gross Axle Weight Rating. The maximum allowable weight that can be carried on the vehicle's axle or individual suspension system, either front or rear. It includes the weight of the vehicle, cargo and equipment supported by the axle and tongue weight when trailering. ⁵ OnStar acts as a link to existing emergency service providers. Not all vehicles may transmit all crash data. Roadside service provided by Allstate Roadside Services, and limitations and restrictions apply. Stolen Vehicle Assistance requires armed, factory-installed theft-deterrent system and selection of notification communication preference(s). These services are intended to assist with vehicle recovery and do not prevent theft or protect against damage or loss. Additional messaging and data rates may apply. Services are subject to user terms and limitations, and vary by vehicle model. Visit onstar.ca for more details. ⁶ Available on select Apple and Android devices. Service availability, features and functionality are subject to limitations and vary by vehicle, device and the plan in which you are enrolled. Device data connection required. Visit onstar.ca for more details. ⁷ Does not monitor spare tire.

11 SILVERADO 1500 CONVENTIONAL TRAILER WEIGHT RATINGS

These charts specify the trailer weight rating for the Silverado 1500 equipped with a conventional hitch. Do not exceed the trailer weight rating.¹ For more information, ask your Chevrolet dealer.

SILVERADO 1500 CONVENTIONAL TRAILER WEIGHT RATINGS¹ – lb. (kg)

ENGINE	AXLE RATIO	GCWR ²	REGULAR CAB		DOUBLE CAB		CREW CAB			
			LONG BOX 2WD	LONG BOX 4x4	STANDARD BOX 2WD	STANDARD BOX 4x4	SHORT BOX 2WD	SHORT BOX 4x4	STANDARD BOX 2WD	STANDARD BOX 4x4
4.3L V6	3.42	12,800 (5806)	7900 (3583)	7700 (3493)	7700 (3493)	7500 (3402)	7700 (3493)	7500 (3402)	7600 (3447)	7400 (3357)
4.3L V6 Trail Boss	3.42	12,800 (5806)	–	–	–	7400 (3357)	–	7300 (3311)	–	7300 (3311)
5.3L V8 (with 6-speed)	3.42	15,000 (6804)	10,100 (4581)	9900 (4491)	9800 (4445)	9600 (4354)	9800 (4445)	9500 (4309)	9700 (4400)	9500 (4309)
5.3L V8 (with 6-speed) Trail Boss	3.42	15,000 (6804)	–	–	–	9500 (4309)	–	9500 (4309)	–	9400 (4264)
2.7L Turbo	3.42	12,000 (5443)	–	–	7000 (3175)	6700 (3039)	6900 (3130)	6700 (3039)	6900 (3130)	6700 (3039)
5.3L V8 (with 8-speed)	3.23	15,000 (6804)	–	–	9900 (4491)	9700 (4400)	9800 (4445)	9600 (4354)	9800 (4445)	9600 (4354)
5.3L V8 (with 8-speed) and Max Trailering Package	3.42	16,800 (7620)	–	–	11,600 (5262)	11,400 (5171)	11,600 (5262)	11,400 (5171)	11,500 (5216)	11,300 (5126)
5.3L V8 Trail Boss	3.23	15,000 (6804)	–	–	–	9500 (4309)	–	9500 (4309)	–	9400 (4264)
6.2L V8	3.23	15,000 (6804)	–	–	–	9300 (4218)	–	9300 (4218)	–	9200 (4173)
6.2L V8 with Max Trailering Package	3.42	17,800 (8074)	–	–	–	12,200 (5534)	–	12,100 (5488)	–	12,000 (5443)

GENERAL TRAILERING NOTES Where available, the Trailering Equipment Package (Z82) provides a trailer hitch platform and 7-pin and 4-pin sealed connectors at the rear bumper.

TRAILER TONGUE WEIGHT NOTES Trailer tongue weight should be 10% to 15% of total loaded trailer weight up to 1250 lb. (567 kg). The addition of trailer tongue weight must not cause vehicle to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR).



¹ Before you buy a vehicle or use it for trailering, carefully review the Trailering section of the Owner's Manual. The weight of passengers, cargo and options or accessories may reduce the amount you can tow. ² Gross Combination Weight Rating (GCWR) is the maximum allowable combined mass of the tow vehicle, passengers and cargo in the tow vehicle, plus the trailer and cargo in the trailer.

12 SILVERADO HD CONVENTIONAL TRAILER WEIGHT RATINGS

These charts specify the trailer weight rating for the Silverado 2500HD/3500HD equipped with a conventional hitch. (For fifth-wheel or gooseneck ratings, see page 13.) Do not exceed the trailer weight rating.¹ For more information, ask your Chevrolet dealer.

SILVERADO 2500HD AND 3500HD CONVENTIONAL TRAILER WEIGHT RATINGS¹ – lb. (kg)

			REGULAR CAB									
ENGINE	AXLE RATIO	GCWR ²	2500HD LONG BOX 4x4									
Vortec 6.0L V8	4.10	21,100 (9571)	14,500 (6577)									
			4-DOOR DOUBLE CAB									
ENGINE	AXLE RATIO	GCWR ²	2500HD LONG BOX 2WD				2500HD STANDARD BOX 4x4			2500HD LONG BOX 4x4		
Vortec 6.0L V8	4.10	21,100 (9571)	14,400 (6532)				13,000 (5897)			14,100 (6396)		
Vortec 6.0L V8	3.73 ³	16,600 (7530)	9900 (4491)				9700 (4400)			9600 (4355)		
			CREW CAB									
ENGINE	AXLE RATIO	GCWR ²	2500HD STANDARD BOX 2WD	2500HD LONG BOX 2WD	3500HD STANDARD BOX 2WD	3500HD LONG BOX 2WD	3500HD LONG BOX 2WD DUALLY	2500HD STANDARD BOX 4x4	2500HD LONG BOX 4x4	3500HD STANDARD BOX 4x4	3500HD LONG BOX 4x4	3500HD LONG BOX 4x4 DUALLY
Vortec 6.0L V8	4.10	21,100 (9571)	13,000 (5897)	14,300 (6486)	13,000 (5897)	14,100 (6396)	13,700 (6214)	13,000 (5897)	13,900 (6305)	13,000 (5897)	13,700 (6214)	13,400 (6078)
Vortec 6.0L V8	3.73 ³	16,600 (7530)	9900 (4491)	9800 (4445)	9700 (4400)	9600 (4355)	9200 (4173)	9600 (4355)	9400 (4264)	9400 (4264)	9200 (4173)	8900 (4037)
Duramax 6.6L V8	3.73	25,300 (11,476)	—	—	13,000 (5897)	14,500 (6577)	—	—	—	13,000 (5897)	15,000 (6804)	—
Turbo-Diesel	3.73	31,300 (14,197)	—	—	—	—	20,000 (9072)	—	—	—	—	20,000 (9072)

GENERAL TRAILERING NOTES Where available, the Trailering Equipment Package (Z82) provides a trailer hitch platform and a 7-pin sealed connector at the rear bumper. A 7-wire camper/fifth-wheel wiring harness (UY2) is also available and requires the Trailering Equipment Package (Z82).

AUTOMATIC TRANSMISSION MODEL NOTE All Silverado models are equipped with an automatic transmission, an engine oil cooler (KC4) and an air-to-oil transmission oil cooler (KNP).

TRAILER TONGUE WEIGHT NOTES Trailer tongue weight should be 10% to 15% of total loaded trailer weight up to 2000 lb. (907 kg). The addition of trailer tongue weight must not cause vehicle to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR).



¹ Before you buy a vehicle or use it for trailering, carefully review the Trailering section of the Owner's Manual. The weight of passengers, cargo and options or accessories may reduce the amount you can tow. ² Gross Combination Weight Rating (GCWR) is the maximum allowable combined mass of the tow vehicle, passengers and cargo in the tow vehicle, plus the trailer and cargo in the trailer. ³ Fleet only.

13 SILVERADO HD FIFTH-WHEEL/GOOSENECK TRAILER WEIGHT RATINGS

These charts specify the trailer weight rating for your vehicle when equipped with a fifth-wheel or gooseneck trailer hitch. (For conventional ratings, see page 12.) The maximum rating for a weight-carrying hitch is listed in the General Trailing Notes below. Do not exceed the trailer weight rating.¹ For more information, ask your Chevrolet dealer.

SILVERADO 2500HD AND 3500HD FIFTH-WHEEL/GOOSENECK TRAILER WEIGHT RATINGS¹ – lb. (kg)

			4-DOOR DOUBLE CAB									
ENGINE	AXLE RATIO	GCWR ²	2500HD LONG BOX 2WD		2500HD STANDARD BOX 4x4				2500HD LONG BOX 4x4			
Vortec 6.0L V8	4.10	21,100 (9571)	14,400 (6532)		14,200 (6441)				14,100 (6396)			
Vortec 6.0L V8	3.73 ³	16,600 (7530)	9900 (4491)		9700 (4400)				9600 (4355)			

			CREW CAB									
ENGINE	AXLE RATIO	GCWR ²	2500HD STANDARD BOX 2WD	2500HD LONG BOX 2WD	3500HD STANDARD BOX 2WD	3500HD LONG BOX 2WD	3500HD LONG BOX 2WD DUALY	2500HD STANDARD BOX 4x4	2500HD LONG BOX 4x4	3500HD STANDARD BOX 4x4	3500HD LONG BOX 4x4	3500HD LONG BOX 4x4 DUALY
Vortec 6.0L V8	4.10	21,100 (9571)	14,300 (6486)	14,200 (6441)	14,200 (6441)	14,000 (6350)	13,700 (6214)	14,000 (6350)	13,900 (6305)	13,900 (6305)	13,700 (6214)	13,300 (6033)
Vortec 6.0L V8	3.73 ³	16,600 (7530)	9800 (4445)	9700 (4400)	9700 (4400)	9500 (4309)	9200 (4173)	9500 (4309)	9400 (4264)	9400 (4264)	9200 (4173)	8800 (3992)
Duramax 6.6L V8	3.73	25,300 (11,476)	–	–	17,500 (7938)	17,400 (7893)	–	–	–	17,200 (7802)	17,000 (7711)	–
Turbo-Diesel	3.73	31,300 (14,197)	–	–	–	–	23,100 (10,478)	–	–	–	–	22,700 (10,297)

GENERAL TRAILERING NOTES Where available, the Trailing Equipment Package (Z82) provides a trailer hitch platform and a 7-pin sealed connector at the rear bumper. A 7-wire camper/fifth-wheel wiring harness (UY2) is also available and requires the Trailing Equipment Package (Z82).

AUTOMATIC TRANSMISSION MODEL NOTE All Silverado models are equipped with an automatic transmission, an engine oil cooler (KC4) and an oil-to-air transmission oil cooler (KNP).

FIFTH-WHEEL/GOOSENECK KINGPIN WEIGHT NOTES

Fifth-wheel or gooseneck kingpin weight should be 15% of total loaded trailer weight. The addition of trailer kingpin weight cannot cause vehicle to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR).

These ratings can be found on the certification label located on the driver door or doorframe. A fifth-wheel hitch is offered on specific models and is also available as a dealer-installed accessory on select models. See Trailing Basics for more trailing information.

FIFTH-WHEEL/GOOSENECK TRAILERING NOTES Silverado HD can be equipped with a fifth-wheel or gooseneck trailer hitch. Follow the manufacturer's directions for installation, but note that the hitch must be attached to the truck frame. Do not use the pickup bed for additional support. For proper kingpin tongue load distribution and control of the trailer, the hitch must be mounted so the kingpin load is placed over, or slightly ahead, of the rear axle centreline. Fifth-wheel trailer kingpin loads are higher than conventional trailer tongue loads, so pay

careful attention to the truck's payload capacity and Rear Gross Axle Weight Rating. Your Chevrolet dealer can help you calculate the maximum allowable payload and GVWR required for your fifth-wheel trailing application. The weight of any additional equipment and all passengers, excluding driver and front passenger, must be subtracted from the payload weight to determine the maximum kingpin load available.

FIFTH-WHEEL/GOOSENECK PREP PACKAGE The Fifth-Wheel/Gooseneck Prep Package (Z6A)⁴ includes a hitch platform ready to accept a gooseneck ball or fifth-wheel hitch, a box-mounted 7-pin trailer harness, a spray-on bedliner and all the necessary box and bedliner holes drilled and capped.



¹ Before you buy a vehicle or use it for trailering, carefully review the Trailing section of the Owner's Manual. The weight of passengers, cargo and options or accessories may reduce the amount you can tow. ² Gross Combination Weight Rating (GCWR) is the maximum allowable combined mass of the tow vehicle, passengers and cargo in the tow vehicle, plus the trailer and cargo in the trailer. ³ Fleet only. ⁴ Requires spray-on bedliner.

14 COLORADO, TAHOE AND SUBURBAN TRAILER WEIGHT RATINGS

These charts specify the trailer weight rating for Colorado, Tahoe and Suburban equipped with a conventional hitch. Do not exceed the trailer weight rating! For more information, ask your Chevrolet dealer.

COLORADO TRAILER WEIGHT RATINGS¹ — lb. (kg)

ENGINE	AXLE RATIO	GCWR ²	EXTENDED CAB 2WD	EXTENDED CAB 4x4	CREW CAB 2WD	CREW CAB 4x4
2.5L I-4	4.10	8500 (3856)	3500 (1588)	3500 (1588)	3500 (1588)	3500 (1588)
3.6L V6	3.42	8500 (3856)	3500 (1588)	3500 (1588)	3500 (1588)	3500 (1588)
3.6L V6 with Trailering Package	3.42	12,000 (5443)	7000 (3175)	7000 (3175)	7000 (3175)	7000 (3175)
Duramax 2.8L I-4 Turbo-Diesel	3.42	12,700 (5761)	—	—	7700 (3493)	7600 (3447)
3.6L V6 with Trailering Package (ZR2)	3.42	10,300 (4672)	—	5000 (2268)	—	5000 (2268)
Duramax 2.8L I-4 Turbo-Diesel (ZR2)	3.42	10,700 (4853)	—	5000 (2268)	—	5000 (2268)

TAHOE/SUBURBAN TRAILER WEIGHT RATINGS¹ — lb. (kg)

ENGINE	AXLE RATIO	GCWR ²	TAHOE 2WD	SUBURBAN 2WD	TAHOE 4x4	SUBURBAN 4x4
EcoTec3 5.3L V8 with Max Trailering Package	3.42	14,000 (6350)	8600 (3901)	8300 (3765)	8400 (3810)	8000 (3629)
EcoTec3 5.3L V8	3.08	12,000 (5443)	6600 (2994)	6300 (2858)	6400 (2903)	6000 (2722)
EcoTec3 6.2L V8	3.23	14,000 (6350)	—	—	8100 (3674)	7900 (3583)

When using a weight-carrying hitch, the maximum trailer weight is 5000 lb. (2268 kg) with a 600 lb. (272 kg) trailer tongue weight. A weight-distributing hitch and sway control are required for trailer tongue weights greater than 600 lb. (272 kg).

NOTES ON COLORADO Trailer tongue weight should be 10% to 15% of total loaded trailer weight (up to 770 lb. [349 kg]). Addition of trailer tongue weight must not cause vehicle weights to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR).

NOTES ON TAHOE AND SUBURBAN Trailer tongue weight should be 10% to 15% of total loaded trailer weight (up to 1000 lb. [454 kg]). Addition of trailer tongue weight must not cause vehicle weights to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR). The standard Heavy-Duty Trailering Package on Tahoe and Suburban includes an auxiliary external transmission fluid cooler and engine oil cooler.



¹ Before you buy a vehicle or use it for trailering, carefully review the Trailering section of the Owner's Manual. The weight of passengers, cargo and options or accessories may reduce the amount you can tow. ² Gross Combination Weight Rating (GCWR) is the maximum allowable combined mass of the tow vehicle, passengers and cargo in the tow vehicle, plus the trailer and cargo in the trailer.

15 TRAVERSE, BLAZER AND EQUINOX TRAILER WEIGHT RATINGS

These charts specify the trailer weight rating for Traverse, Blazer and Equinox equipped with a conventional hitch. Do not exceed the trailer weight rating! For more information, ask your Chevrolet dealer.

TRAVERSE TRAILER WEIGHT RATINGS¹ – lb. (kg)

ENGINE	AXLE RATIO	GCWR ²	FWD	AWD
3.6L V6 FWD	3.49	10,030 (4550)	5000 (2268)	–
3.6L V6 AWD	3.49	10,250 (4649)	–	5000 (2268)

When using a weight-carrying hitch, the maximum trailer weight is 5000 lb. (2268 kg) with a 600 lb. (272 kg) trailer tongue weight. A weight-distributing hitch and sway control are required for trailer weights greater than 5000 lb. (2268 kg).

BLAZER TRAILER WEIGHT RATINGS¹ – lb. (kg)

ENGINE	AXLE RATIO	GCWR ²	FWD	AWD
2.5L I-4 FWD	3.80	5787 (2625)	1500 (680)	–
3.6L V6 FWD	3.49	5787 (2625)	1500 (680)	–
3.6L V6 AWD	3.49	9250 (4155)	–	4500 (2041)

EQUINOX TRAILER WEIGHT RATINGS¹ – lb. (kg)

ENGINE	AXLE RATIO	GCWR ²	FWD	AWD
1.5L I-4 Turbo FWD	3.50	5247 (2380)	1500 (680)	–
1.5L I-4 Turbo AWD	3.87	5467 (2480)	–	1500 (680)
2.0L I-4 Turbo AWD	3.17	7694 (3490)	–	3500 (1587)
1.6L I-4 Turbo-Diesel FWD	2.89	5687 (2580)	1500 (680)	–
1.6L I-4 Turbo-Diesel AWD	2.89	5687 (2580)	–	1500 (680)

Weight-distributing hitch and sway control not required.

NOTES ON TRAVERSE Trailer tongue weight should be 10% to 15% of total loaded trailer weight (up to 600 lb. [272 kg]). Addition of trailer tongue weight must not cause vehicle weights to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR). Maximum trailer weight rating requires the factory-installed Trailering Package.

NOTES ON BLAZER Trailer tongue weight should be 10% to 15% of total loaded trailer weight (up to 450 lb. [204 kg]). Addition of trailer tongue weight must not cause vehicle weights to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR). Maximum trailer weight rating requires the available trailering equipment.

NOTES ON EQUINOX Trailer tongue weight should be 10% to 15% of total loaded trailer weight (up to 350 lb. [159 kg]). Addition of trailer tongue weight must not cause vehicle weights to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR). Maximum trailer weight rating requires the available Trailering Package.



¹ Before you buy a vehicle or use it for trailering, carefully review the Trailering section of the Owner's Manual. The weight of passengers, cargo and options or accessories may reduce the amount you can tow. ² Gross Combination Weight Rating (GCWR) is the maximum allowable combined mass of the tow vehicle, passengers and cargo in the tow vehicle, plus the trailer and cargo in the trailer.

16 EXPRESS PASSENGER VAN AND EXPRESS CARGO VAN TRAILER WEIGHT RATINGS

These charts specify the trailer weight rating for Express Passenger Van and Express Cargo Van equipped with a conventional hitch. Do not exceed the trailer weight rating¹ For more information, ask your Chevrolet dealer.

EXPRESS PASSENGER VAN TRAILER WEIGHT RATINGS¹ – lb. (kg)

ENGINE	AXLE RATIO	GCWR ²	2500	3500	3500 EXTENDED WHEELBASE
4.3L V6	3.42	13,000 (5897)	6700 (3039)	6700 (3039)	6300 (2858)
Vortec 6.0L V8	3.42	16,000 (7258)	9600 (4354)	9600 (4354)	9200 (4173)
Duramax 2.8L Turbo-Diesel	3.42	13,000 (5897)	6300 (2858)	5700 (2585)	5300 (2404)

When using a weight-carrying hitch, the maximum trailer weight is 5000 lb. (2268 kg) with a 600 lb. (272 kg) tongue weight. A weight-distributing hitch and sway control are required for trailer weights greater than 5000 lb. (2268 kg).

EXPRESS CARGO VAN TRAILER WEIGHT RATINGS¹ – lb. (kg)

ENGINE	AXLE RATIO	GCWR ²	2500	2500 EXTENDED WHEELBASE	3500	3500 EXTENDED WHEELBASE
4.3L V6	3.42	13,000 (5897)	7400 (3357)	7100 (3221)	7400 (3357)	7200 (3266)
Vortec 6.0L V8	3.42	16,000 (7258)	10,000 (4536)	10,000 (4536)	10,000 (4536)	10,000 (4536)
Duramax 2.8L Turbo-Diesel 4-cylinder	3.42	13,000 (5897)	7000 (3175)	6100 (2767)	6200 (2812)	6000 (2722)

When using a weight-carrying hitch, the maximum trailer weight is 5000 lb. (2268 kg) with a 600 lb. (272 kg) tongue weight. A weight-distributing hitch and sway control are required for trailer weights greater than 5000 lb. (2268 kg).

NOTES ON EXPRESS Trailer tongue weight should be 10% to 15% of total loaded trailer weight (up to 1000 lb. [454 kg]). Addition of trailer tongue weight cannot cause vehicle weights to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR). The standard base cooling system includes all content required to attain maximum trailer weight rating. No optional cooling equipment is available. The Heavy-Duty Trailering Equipment Package (Z82) includes trailer hitch platform and 7-wire trailer wiring harness.



¹ Before you buy a vehicle or use it for trailering, carefully review the Trailering section of the Owner's Manual. The weight of passengers, cargo and options or accessories may reduce the amount you can tow. ² Gross Combination Weight Rating (GCWR) is the maximum allowable combined mass of the tow vehicle, passengers and cargo in the tow vehicle, plus the trailer and cargo in the trailer.

17 CHASSIS CAB AND EXPRESS CUTAWAY GROSS COMBINATION WEIGHT RATINGS — lb. (kg)

SILVERADO 3500HD CHASSIS CAB

ENGINE	AXLE RATIO	GCWR ¹
Vortec 6.0L V8	3.73	16,600 (7530)
Vortec 6.0L V8	4.10	21,100 (9571)
6.6L V8 Duramax Turbo-Diesel	3.73	31,300 (14,197)

Available on WT or LT Regular Cab or Crew Cab models.

EXPRESS CUTAWAY

ENGINE	AXLE RATIO	GCWR ¹
4.3L V6	3.42	13,000 (5897)
Vortec 6.0L V8	3.42	16,000 (7258)
	3.73	16,000 (7258)
	4.10	20,000 (9072)

Available on 3500 or 4500 models.

NOTES ON CHASSIS CAB AND EXPRESS CUTAWAY:
GROSS COMBINATION WEIGHT RATINGS Chevrolet engineers perform extensive testing of acceleration, handling, braking, and thermal and structural performance to determine the Gross Combination Weight Rating (GCWR) for your vehicle. The GCWR is the total allowable weight of the completely loaded vehicle and trailer including any passengers, cargo, equipment and conversions. You should not exceed the GCWR of your vehicle when you tow a trailer.

Because the GCWR is calculated for a line of vehicles, rather than an individual load situation, some standardized assumptions are made. First, the base curb weight of that type of vehicle is used (the weight of a standard equipped vehicle without any options). Second, it is assumed that there is only one person in the vehicle (the driver) who weighs 150 lb. (68 kg).



¹ Gross Combination Weight Rating (GCWR) is the maximum allowable combined mass of the tow vehicle, passengers and cargo in the tow vehicle, plus the trailer and cargo in the trailer.

18 DINGHY TOWING

DINGHY TOWING Many motor home drivers like to dinghy-tow a smaller vehicle as they travel. The chart below shows which Chevrolet vehicles can be dinghy-towed without a dolly or trailer and with all four wheels on the ground. Towed vehicles (or dollies or trailers carrying them) should have a separate functional braking system.

DINGHY TOWING SETUP PROCEDURE Use extra caution whenever towing another vehicle. Do not exceed the towing vehicle's ratings such as the Gross Combination Weight Rating (GCWR) by adding the weight of the dinghy-towed vehicle or vehicle damage may result.

SPECIFIC DINGHY TOWING INSTRUCTIONS FOR COLORADO AND SILVERADO 4x4 MODELS WITH A 2-SPEED TRANSFER CASE (WITH A NEUTRAL AND A 4-LOW POSITION):

1. Tow only in a forward direction. Position the vehicle to be towed behind the towing vehicle.
2. Securely attach the vehicle to the tow vehicle.
3. Firmly apply the parking brake, start the engine and shift the transmission to Neutral. Caution: Shifting the transmission to Neutral can cause the vehicle to roll and may cause personal injury.

4. Shift the transfer case to Neutral. Caution: Shifting the transfer case to Neutral can cause the vehicle to roll, even if the transmission is in Park (automatic), and may cause personal injury. SEE YOUR VEHICLE OWNER'S MANUAL FOR SPECIFIC INSTRUCTIONS ON SHIFTING IN AND OUT OF NEUTRAL.
5. Check for transfer case Neutral by shifting transmission to Reverse, then Drive, and verify that there is no engagement.
6. While the transmission is in Drive, turn the ignition key to Accessory.
7. Shift the transmission to Park.
8. Depower the vehicle by removing the negative cable at the battery. This procedure must be followed or the steering column could be damaged.
9. Cover the negative battery post with a nonconducting material and prevent any contact between the negative battery terminal and the negative battery cable.
Notice: If power is provided by accidental contact of the cable and terminals, damage to the towed vehicle may result, which would not be covered under the New Vehicle Limited Warranty.

10. Verify the steering column is unlocked.
11. Release the parking brake only after verifying the towed vehicle is attached to the towing vehicle.
12. The ignition key must remain in the towed vehicle.
Manually lock the doors and use second key for access.

NOTE ON DINGHY TOWING If equipped with Keyless Access, keep the RKE transmitter outside of the vehicle and manually lock the doors. Access the vehicle as if it has a dead RKE transmitter battery by using the key in the door lock.

DISCONNECTING THE TOWED VEHICLE FOR COLORADO AND SILVERADO 4x4s

1. Park on a level surface. Secure the vehicle with wheel blocks.
2. Connect the battery.
3. Turn on the ignition with the engine off.
4. Set the parking brake.
5. Shift the transfer case to 2 HI.
6. Disconnect the vehicle from the tow vehicle.
7. Start the engine of the towed vehicle.
8. Shift the transmission to Park and turn off the ignition.
9. Release the parking brake and remove the wheel blocks.
10. Reset any lost presets.

DINGHY (FLAT) TOWING CAPABILITY

	BLAZER	BOLT EV	CAMARO	COLORADO	CORVETTE	CRUZE	EQUINOX	EXPRESS	IMPALA	MALIBU	SILVERADO	SPARK	SUBURBAN	TAHOE	TRAVERSE	TRAX	VOLT
2WD	Yes	No	No	No	No	No	Yes	No	No	Yes ²	No	Yes ⁴	No	No	Yes	No	No
4x4	–	–	–	Yes	–	–	–	–	–	–	Yes ³	–	Yes ³	Yes ³	–	–	–
AWD	Yes	–	–	–	–	–	Yes ¹	–	–	–	–	–	–	–	Yes	No	–



¹ 1.6L Turbo-Diesel and 2.0L turbo models. ² Malibu Premier model only. ³ Requires available 2-speed transfer case. ⁴ With manual transmission only.

19 CLOSING REMARKS

TRAILERING WITH YOUR CHEVROLET Chevrolet vehicles are built strong and durable to handle the demands of trailering. Certain equipment that prepares a Chevrolet vehicle for trailering is standard: a large fuel tank, a high-capacity alternator and a front stabilizer bar. For other available trailering-related equipment, talk to your dealer. You'll need a hitch, of course, and a wide selection of hitch types are available, either as factory equipment or from your dealer. In addition, if you plan to tow frequently, you should equip your Chevrolet vehicle with the available Trailering Package. This package includes a trailer hitch platform and an electrical harness. Also required with this package are a hitch ball, a mounting head, and possibly weight-distributing and anti-sway assemblies; these are available through aftermarket sources. Please carefully review your Chevrolet vehicle Owner's Manual for important safety information about trailering with your vehicle.

WORDS ABOUT THIS GUIDE We have tried to make this guide comprehensive and factual. We reserve the right, however, to make changes at any time and without notice in prices, colours, materials, equipment, specifications, models and availability. Information may have been updated since the time of publication. Please check with your Chevrolet dealer for complete details. Chevrolet reserves the right to lengthen or shorten the model year for any product for any reason, or to start and end model years at different times. Chevrolet vehicles are equipped with engines produced by GM Propulsion Systems or other suppliers to General Motors worldwide. The marks appearing in this brochure including, but not limited to, General Motors, GM, Chevrolet, the Chevrolet emblem, Blazer, Bolt EV, Camaro, Colorado, Corvette, Cruze, Equinox, Express, Impala, Malibu, Silverado, Spark, Suburban, Tahoe, Traverse, Trax, Volt and their respective logos, emblems, slogans and vehicle model names and body designs; and other marks such as Duramax, myChevrolet, OnStar, StabiliTrak and Vortec are trademarks of General Motors LLC and/or General Motors of Canada Company, its subsidiaries, affiliates or licensors. ©2019 General Motors. All rights reserved.

