

2014
CHALLENGER SRT®



SRT

MODERN MARVEL. LEGENDARY DNA.

2014 CHALLENGER SRT®

\$49,795 MSRP†

AWE INSPIRING POWERTRAIN

- 6.4L SRT 392 HEMI® V8
- FuelSaver MDS Technology allows the engine to seamlessly deactivate four cylinders when eight are not needed, creating the perfect balance of power, efficiency and wise fuel consumption
- DISPLACEMENT 6424 cu cm (392 cu in)
- POWER..... 470 hp @ 6000 rpm
- TORQUE 470 lb-ft @ 4300 rpm
- TRANSMISSION 5-speed automatic with paddle shifters
- TRANSMISSION Optional Tremec® 6-speed manual
- FINAL DRIVE RATIO (Automatic) 3.06:1
- FINAL DRIVE RATIO (Manual) 3.92:1

RACE INSPIRED AND HIGH PERFORMANCE INTERIOR

- Performance Nappa leather-faced seats with perforated suede inserts available in Black or Radar Red
- Heated SRT embroidered front seats
- Heated, leather wrapped, flat-bottom SRT steering wheel with available race-inspired paddle shifters
- Metallic, race inspired pedals
- Uconnect™ 430 with 6.5-inch touch-screen, 28GB hard drive and SRT Performance Pages
- Six Boston Acoustics® speakers with 276-watt amplifier
- Available 18 speaker harman/kardon® audio system with two 10-inch subwoofers and 900-watt amplifier

1. Drive Responsibly. Always obey the rules of the road 2. No system can repeal the laws of physics or overcome careless driving actions. Performance is limited by available traction, which snow, ice and other conditions can affect. When the warning lamp flashes, the driver needs to use less throttle and adapt speed and driving behaviour to prevailing road conditions. †Prices as shown are MSRP. Excludes freight (\$1,695), air tax (\$100), insurance, registration, license, retailer administration fees, new tire. Duties in Quebec and dealer accessories are not included. Retailer may sell for less.

OUTSTANDING RIDE AND HANDLING

- Antispin rear differential
- Three-mode adaptive damping suspension
- Three-mode Electronic Stability Control⁽¹⁾ with knock-back mitigation
- Launch control provides enhanced straight-line acceleration⁽²⁾
- Performance tuned steering and suspension

BENCHMARK BRAKING

- Performance four-wheel disc ABS brakes
- FRONT ROTORS, in (mm) 14.2 x 1.26 (360 x 32), vented and slotted
- REAR ROTORS, in (mm) 13.8 x 1.10 (350 x 28), vented and slotted
- CALIPERS Brembo® four-piston fixed with aluminum housing

AGGRESSIVE AND FUNCTIONAL EXTERIOR

- 20-inch forged aluminum five-spoke SRT design wheels
- Available 20-inch Black Vapour SRT Design wheels
- Dual integrated 4-inch exhaust tips
- Functional hood scoop
- Dual centre stripes in: Black, Red, Silver, or Grey

PERFORMANCE SPECIFICATIONS⁽²⁾

- 0-TO-100 KM/H in the 4s
- 0-TO-160 KM/H-TO-0 under 16 seconds
- 400 METRES (1/4 MILE) in the 12s
- 100 KM-TO-0 36 metres
- TOP SPEED 290 KM/H

